

IN THE CLAIMS:

Please cancel Claims 3, 14, 19, 24, and 38, without prejudice or disclaimer of the subject matter presented therein.

Please amend Claims 1, 2, 4, 5, 7-13, 15, 17, 18, 20-23, 25-29, 31-37, 39, and 41-51 as follows:

Sub C  
1. (Amended) A data transmission method for host and target devices[, ] connected by a serial bus, said method comprising the steps of:

performing bi-directional communication between [said] the host and target devices; and

selectively setting a data transfer method to be performed from a plurality of data transfer methods including a [PULL model in which said target device reads data from said host device, based on] synchronous transfer method, which performs flow control, and an asynchronous transfer method by using the bi-directional communication,

wherein the data transfer method is set by the host device in accordance with a data transfer method set in the target device.

2. (Amended) The method according to claim 1, wherein the plurality of data transfer methods [further include]

includes a PULL model, in which the target device reads data from the host device, a response model, in which a response is returned in a unit of block transfer, a simplified response model, in which a response of the simplified response model is to simplify, a [Push] PUSH model, in which [said] the host device writes data into [said] the target device, and an [Isochronous] isochronous model [using], which uses an isochronous transfer.

3/4. (Amended) The method according to claim [1] 2, wherein the PULL model is a PULL data transfer method in which data transfer is performed by reading data of [said] the host device by [said] the target device.

4/5. (Amended) The method according to claim 1, wherein the serial bus is a bus adapted to or based on [the] IEEE 1394 standards.

6/7. (Amended) The method according to claim 1, wherein [said] the host device provides image data.

7/8. (Amended) The method according to claim [1] 6/7, wherein [said] the target device forms a visible image, based on the image data, on a print medium.

8. (Amended) The method according to claim [1] <sup>6</sup>/<sub>1</sub>,

wherein [said] the target device stores the image data into a storage medium.

Sub  
C2

10. (Amended) An image processing apparatus

comprising:

communication means for performing communication with a target device by [the data transfer method in claim 1]:

performing bi-directional communication between a host device and the target device, and

selectively setting a data transfer method to be performed from a plurality of data transfer methods including a synchronous transfer method, which performs flow control, and an asynchronous transfer method by using the bi-directional communication, wherein the data transfer method is set by the host device in accordance with a data transfer method set in the target device; and

transmission means for transmitting image data to [said] the target device via said communication means.

11. (Amended) An image processing apparatus

comprising:

communication means for performing communication with a host device by [the data transfer method in claim 1]:

Sub  
C2  
performing bi-directional communication between  
the host device and a target device, and

selectively setting a data transfer method to be  
performed from a plurality of data transfer methods including a  
synchronous transfer method, which performs flow control, and an  
asynchronous transfer method by using the bi-directional  
communication, wherein the data transfer method is set by the  
host device in accordance with a data transfer method set in the  
target device; and

processing means for processing image data received  
from [said] the host device via said communication means.

12. (Amended) A data transmission apparatus  
connected to a serial bus, comprising:

Sub  
B2  
communication means for performing bi-directional  
communication with a target device; and

setting means for selectively setting a data transfer  
method to be performed from a plurality of data transfer [method]  
methods including a [PULL model, based on] synchronous transfer  
method, which performs flow control, and an asynchronous transfer  
method by using the bi-directional communication,

wherein the data transfer method is set in accordance  
with a data transfer method set in the target device.

12  
13. (Amended) The apparatus according to claim 12,  
wherein the plurality of data transfer methods [further include]  
includes a PULL mode, in which the target device reads data from  
the apparatus, a response model, in which a response is returned  
in a unit of block transfer, a simplified response model, in  
which a response of the simplified response model is to simplify,  
a PUSH model, in which the apparatus writes data into the target  
device, and an isochronous model, which uses an isochronous  
transfer.

13  
14. (Amended) The apparatus according to claim 13,  
wherein the PULL model is a PULL data transfer method in  
which data transfer is performed by reading data of [said host  
device] said apparatus by [said] the target device.

Sub B3 AS  
17. (Amended) A data transmission apparatus  
connected to a serial bus, said apparatus comprising:  
communication means for performing bi-directional  
communication with a host device; and  
transfer means for performing data transfer with  
[said] the host device by a data transfer method selectively set  
from a plurality of data transfer [method] methods including a  
[PULL model, based on] synchronous transfer method, which  
performs flow control, and an asynchronous transfer method by

using the bi-directional communication,

wherein the data transfer method is set by the host device in accordance with a data transfer method set in the apparatus.

16

18. (Amended) The apparatus according to claim 15,

wherein the plurality of data transfer methods [further include] includes a PULL model, in which said apparatus reads data from the host device, a response model, in which a response is returned in a unit of block transfer, a simplified response model, in which a response of the simplified response model is to simplify, a PUSH model, in which the host device writes data into said apparatus, and an isochronous model, which uses an isochronous transfer.

17

20. (Amended) The apparatus according to claim [17] 18, wherein the PULL model is a PULL data transfer method in which data transfer is performed by reading data of [said] the host device by said [target device] apparatus.

21. (Amended) The apparatus according to claim 17, further comprising formation means for forming a visible image on a print medium based on data received by said transfer means [on a print medium].

Sub B  
24  
22. (Amended) A data transmission system for transferring data through a serial bus, comprising:

communication means for performing bi-directional communication between host and target devices; and

setting means for selectively setting a data transfer method to be [set] performed from a plurality of data transfer methods, including a [PULL model, based on] synchronous transfer method, which performs flow control, and an asynchronous transfer method by using the bi-directional communication,

wherein the data transfer method is set by the host device in accordance with a data transfer method set in the target device.

20

23. (Amended) The system according to claim 19, wherein the plurality of data transfer methods [further include] includes a PULL model, in which the target device reads data from the host device, a response model, in which a response is returned in a unit of block transfer, a simplified response model, in which a response of the simplified response model is to simplify, a PUSH model, in which the host device writes data into the target device, and an isochronous model, which uses an isochronous transfer.

20

Sub B  
24  
25. A data transmission method of host and target

devices which are connected by a serial bus, said method comprising the steps of:

transferring data from [said] the host device to [said] the target device, by using a transfer method selected by the host device from an isochronous transfer [or] method and an asynchronous transfer method in accordance with a data transfer method set in the target device; and

transferring a procedure signal for transfer of the data to [said] the host and target devices by a common asynchronous transfer.

22  
26. (Amended) The method according to claim 25,  
wherein the asynchronous transfer method includes a Push Buffer model, in which [said] the host device writes data into [said] the target device, and a Pull Buffer model, in which [said] the target device reads data from [said] the host device.

23  
27. (Amended) The method according to claim 25,  
wherein said host device sets [a] the data transfer method corresponding to [said] the target device, based on the procedure signal transferred [by] in the common asynchronous transfer.

24  
28. (Amended) The method according to claim 25,  
wherein [said] the host device selects the [isochronous transfer



or the asynchronous] data transfer method based on the procedure  
signal transferred [by] in the common asynchronous transfer.

25  
29. (Amended) The method according to claim 21,  
wherein the serial bus is a bus adapted to or based on [the] IEEE  
1394 standards.

27  
31. (Amended) The method according to claim 25,  
wherein [said] the host device provides image data.

28  
32. (Amended) The method according to claim 21,  
wherein [said] the target device forms a visible image[, ] on a  
print medium based on the image data[, on a print medium].

29  
33. (Amended) The method according to claim [25] 31,  
wherein [said] the target device stores the image data into a  
storage medium.

34. (Amended) An image processing apparatus  
comprising:  
communication means for performing communication with  
a target device by [the data transfer method in claim 25]  
transferring data from a host device to the  
target device, by using a transfer method selected by the host

device from an isochronous transfer method and an asynchronous transfer method in accordance with a data transfer method set in the target device, and

transferring a procedure signal for transfer of the data to the host and target devices by a common asynchronous transfer; and

transmission means for transmitting image data to [said] the target device via said communication means.

35. (Amended) An image processing apparatus comprising:

communication means for performing communication with a host device by [the data transfer method in claim 25]

transferring data from the host device to a target device, by using a transfer method selected by the host device from an isochronous transfer method and an asynchronous transfer method in accordance with a data transfer method set in the target device, and

transferring a procedure signal for transfer of the data to the host and target devices by a common asynchronous transfer; and

processing means for processing image data received from [said] the host device via said communication means.

36. (Amended) A data transmission apparatus  
connected to a serial bus, comprising:

transfer means for transferring a procedure signal  
for data transfer by a common asynchronous transfer [common] to a  
target device; and

transmission means for transmitting data to be  
transmitted to [said] the target device by using a transfer  
method, which is selected from an isochronous [transmission or]  
transfer method and an asynchronous [transmission] transfer  
method, in accordance with a data transfer method set in the  
target device.

32

37. (Amended) The apparatus according to claim <sup>31</sup>35,  
wherein the [isochronous] asynchronous transfer method includes a  
PUSH buffer model and a PULL buffer model.

39. (Amended) The apparatus according to claim 36,  
wherein said transmission means selects the isochronous transfer  
method or the asynchronous transfer[,]  
method based on the  
procedure signal transferred by the common asynchronous transfer.

41. (Amended) A data transmission apparatus  
connected to a serial bus, comprising:

transfer means for transferring a procedure signal

for data transfer by a common asynchronous transfer [common] to a host device; and

reception means for receiving data from [said] the host device by using a transfer method selected by the host device from an isochronous transfer [or] method and an asynchronous transfer method in accordance with a data transfer method set in said apparatus.

37 42. (Amended) The apparatus according to claim 41, wherein the asynchronous transfer method includes a PUSH buffer model and a PULL buffer model.

sub B7 A10 43. (Amended) The apparatus according to claim 41, wherein [said] the host device sets [a] the data transfer method corresponding to said reception means[, ] based on the procedure signal transferred by the common asynchronous transfer.

39 44. (Amended) The apparatus according to claim 41, wherein [said] the host device selects the [isochronous transfer or the asynchronous] data transfer method based on the procedure signal transferred by the common asynchronous transfer.

sub B7 45. (Amended) The apparatus according to claim 41, further comprising formation means for forming a visible image on

a print medium based on data received by said reception means [on a print medium].

46. (Amended) A data transmission system for transferring data through a serial bus, comprising:

first transfer means for transferring a procedure signal for data transfer by common asynchronous transfer to host and target devices; and

second transfer means for performing data transfer between said host and target devices by using a transfer method selected by the host device from an isochronous transfer [or the] method or an asynchronous transfer method in accordance with a data transfer method set in the target device.

42  
47. (Amended) The system according to claim 41, wherein the asynchronous transfer method includes a PUSH Buffer model and a PULL Buffer model.

43  
48. (Amended) The system according to claim 41, wherein [said] the host device sets [a] the data transfer method corresponding to [said] the target device, based on the procedure signal transferred by the common asynchronous transfer.

44  
49. (Amended) The system according to claim 41,

wherein [said] the host device selects the [isochronous transfer or the asynchronous] data transfer method based on the procedure signal transferred by the common asynchronous transfer.

50. (Amended) A computer program product comprising a computer readable medium [having] storing computer program codes[, ] for executing data transmission of host and target devices which are connected by a serial bus, said product comprising:

communication process procedure codes for performing bi-directional communication between [said] the host and target devices; and

setting process procedure codes for selectively setting a data transfer method to be performed from a plurality of data transfer methods including a [PULL model] synchronous transfer method, which performs flow control, and an asynchronous transfer method by using the bi-directional communication,

wherein the data transfer method is set by the host device in accordance with a data transfer method set in the target device.

51. (Amended) A computer program product comprising a computer readable medium [having] storing computer program codes[, ] for executing data transmission of host and target